



For Listing/Approval Details and Limitations, visit our website at [www.anvilstar.com](http://www.anvilstar.com) or contact an Anvil®/AnvilStar™ Sales Representative.

**FIGURE 7050DR 90° DRAIN ELBOW**

Nominal Size	O.D.	Max. Working Pressure	Dimensions		Approx. Wt. Ea.
			Center to End	H	
In./DN(mm)	In./mm	PSI/bar	In./mm	In./mm	Lbs./Kg
1¼ 32	1.660 42.2	300 20.7	2¾ 70	1¾ 44	2.1 1.0
1½ 40	1.900 48.3	300 20.7	2¾ 70	1¾ 44	2.5 1.1
2 50	2.375 60.3	300 20.7	3¼ 83	1¾ 44	2.9 1.3
2½ 65	2.875 73.0	300 20.7	3¾ 95	1¾ 48	5.2 2.4
3 80	3.500 88.9	300 20.7	4¼ 108	2 51	7.5 3.4
4 100	4.500 114.3	300 20.7	5 127	2¼ 57	12.2 5.5
5 125	5.563 141.3	300 20.7	5½ 140	2¾ 60	17.6 8.0
6 150	6.625 168.3	300 20.7	6½ 165	2¾ 60	28.3 12.8
8 200	8.625 219.1	300 20.7	7¾ 197	2½ 64	48.0 21.8
10 250	10.750 273.1	300 20.7	9 229	2¾ 69	70.0 31.8
12 300	12.750 323.9	300 20.7	10 254	2¾ 69	110 49.9

Additional sizes available, see Gruklok Catalog or contact an AnvilStar Representative.

☞ - Available galvanized.

Available fabricated Schedule 10 only.

Drain elbow has a standard 1" female NPT outlet.

**MATERIAL SPECIFICATIONS**

**FABRICATED FITTINGS:**

1¼" - 6" are Carbon Steel, A-135, Schedule 10

8" - 12" are Carbon Steel, A-795/A-135/.188 Wall

**COATINGS:**

Rust inhibiting paint Color: ORANGE (standard) or

Hot Dipped Zinc Galvanized conforming to ASTM A-153 (optional)

Other available options: Example: RAL3000 or RAL9000 Series

**PROJECT INFORMATION**

**APPROVAL STAMP**

<b>Project:</b>	<input type="checkbox"/> Approved
<b>Address:</b>	<input type="checkbox"/> Approved as noted
<b>Contractor:</b>	<input type="checkbox"/> Not approved
<b>Engineer:</b>	<b>Remarks:</b>
<b>Submittal Date:</b>	
<b>Notes 1:</b>	
<b>Notes 2:</b>	