



For Listing/Approval Details and Limitations, visit our website at [www.anvilstar.com](http://www.anvilstar.com) or contact an Anvil®/AnvilStar™ Sales Representative.

**FIGURE 7050S\*  
STANDARD 90° ELBOW**

Nominal Size	O.D.	Max. Rated Pressure	Center to End	Approx. Wt. Ea.
In./DN(mm)	In./mm	PSI/bar	In./mm	Lbs./Kg
1¼ 32	1.660 42.2	300 20.7	2¾ 70	1.0 0.5
1½ 40	1.900 48.3	300 20.7	2¾ 70	1.2 0.5
2 50	2.375 60.3	300 20.7	3¼ 83	1.7 0.8
2½ 65	2.875 73.0	300 20.7	3¾ 95	2.6 1.2
3 80	3.500 88.9	300 20.7	4¼ 108	4.0 1.8
4 100	4.500 114.3	300 20.7	5 127	7.7 3.5
5 125	5.563 141.3	300 20.7	5½ 140	11.1 5.0
6 150	6.625 168.3	300 20.7	6½ 165	16.5 7.5
8 200	8.625 219.1	300 20.7	7¾ 197	30.6 13.9

For additional sizes, see Fig. 7050 in the Gruvlok Catalog or contact an AnvilStar Representative.

- Available galvanized.

\* When ordering, refer to product as FP7050S.

These fittings are designed to provide minimal pressure drop and uniform strength.

**MATERIAL SPECIFICATIONS**

**CAST FITTINGS:**

Ductile Iron conforming to ASTM A-536  
Malleable Iron conforming to ASTM A-47

**COATINGS:**

Rust inhibiting paint Color: ORANGE (standard) or  
Hot Dipped Zinc Galvanized conforming to ASTM A-153 (optional)  
Other available options: Example: RAL3000 or RAL9000 Series

Not for use in copper systems.

**PROJECT INFORMATION**

**APPROVAL STAMP**

<b>Project:</b>	<input type="checkbox"/> Approved
<b>Address:</b>	<input type="checkbox"/> Approved as noted
<b>Contractor:</b>	<input type="checkbox"/> Not approved
<b>Engineer:</b>	<b>Remarks:</b>
<b>Submittal Date:</b>	
<b>Notes 1:</b>	
<b>Notes 2:</b>	