



For Listing/Approval Details and Limitations, visit our website at www.anvilstar.com or contact an Anvil®/AnvilStar™ Sales Representative.

**FIGURE 7051*
STANDARD 45° ELBOW**

Nominal Size	O.D.	Max. Rated Pressure	Center to End	Approx. Wt. Ea.
In./DN(mm)	In./mm	PSI/bar	In./mm	Lbs./Kg
1¼	1.660	300	1¾	0.7
32	42.2	20.7	44	0.3
1½	1.900	300	1¾	0.9
40	48.3	20.7	44	0.4
2	2.375	300	2	1.5
50	60.3	20.7	51	0.7
2½	2.875	300	2¼	1.9
65	73.0	20.7	57	0.9
3	3.500	300	2½	3.3
80	88.9	20.7	64	1.5
4	4.500	300	3	5.4
100	114.3	20.7	76	2.4
5	5.563	300	3¼	9.0
125	141.3	20.7	83	4.1
6	6.625	300	3½	11.2
150	168.3	20.7	89	5.1
8	8.625	300	4¼	19.8
200	219.1	20.7	108	9.0

Additional sizes available, see Gruklok Catalog or contact an AnvilStar Representative.

Available as a fabricated fitting.

– Available galvanized.

* When ordering, refer to product as FP7051.

These fittings are designed to provide minimal pressure drop and uniform strength.

MATERIAL SPECIFICATIONS

CAST FITTINGS:

Ductile Iron conforming to ASTM A-536

Malleable Iron conforming to ASTM A-47

COATINGS:

Rust inhibiting paint Color: ORANGE (standard) or

Hot Dipped Zinc Galvanized conforming to ASTM A-153 (optional)

Other available options: Example: RAL3000 or RAL9000 Series

Not for use in copper systems.

PROJECT INFORMATION

APPROVAL STAMP

Project:	<input type="checkbox"/> Approved
Address:	<input type="checkbox"/> Approved as noted
Contractor:	<input type="checkbox"/> Not approved
Engineer:	Remarks:
Submittal Date:	
Notes 1:	
Notes 2:	