



For Listing/Approval Details and Limitations, visit our website at www.anvilstar.com or contact an Anvil®/AnvilStar™ Sales Representative.

FIGURE 7060S* STANDARD TEE

Nominal Size	O.D.	Max. Rated Pressure	Center to End	Approx. Wt. Ea.
In./DN(mm)	In./mm	PSI/bar	In./mm	Lbs./Kg
1¼ 32	1.660 42.2	300 20.7	2¾ 70	1.5 0.7
1½ 40	1.900 48.3	300 20.7	2¾ 70	1.8 0.8
2 50	2.375 60.3	300 20.7	3¼ 83	2.4 1.1
2½ 65	2.875 73.0	300 20.7	3¾ 95	4.0 1.8
3 80	3.500 88.9	300 20.7	4¼ 108	5.8 2.6
4 100	4.500 114.3	300 20.7	5 127	10.3 4.7
5 125	5.563 141.3	300 20.7	5½ 140	16.2 7.3
6 150	6.625 168.3	300 20.7	6½ 165	25.7 11.7
8 200	8.625 219.1	300 20.7	7¾ 197	41.1 18.6

Additional sizes available, see Gruvlok Catalog or contact an AnvilStar Representative.

– Available galvanized.

* When ordering, refer to product as FP7060S.

These fittings are designed to provide minimal pressure drop and uniform strength.

MATERIAL SPECIFICATIONS

CAST FITTINGS:

Ductile Iron conforming to ASTM A-536
Malleable Iron conforming to ASTM A-47

COATINGS:

Rust inhibiting paint Color: ORANGE (standard) or
Hot Dipped Zinc Galvanized conforming to ASTM A-153 (optional)
Other available options: Example: RAL3000 or RAL9000 Series

PROJECT INFORMATION

APPROVAL STAMP

Project:	<input type="checkbox"/> Approved
Address:	<input type="checkbox"/> Approved as noted
Contractor:	<input type="checkbox"/> Not approved
Engineer:	Remarks:
Submittal Date:	
Notes 1:	
Notes 2:	