



For Listing/Approval Details and Limitations, visit our website at www.anvilstar.com or contact an Anvil®/AnvilStar™ Sales Representative.

- Available galvanized.

* When ordering, refer to product as FP7074.

FIGURE 7074 CAP

Nominal Size	O.D.	End to End	Approx. Wt. Ea.
In./DN(mm)	In./mm	In./mm	Lbs./Kg
1¼ 32	1.660 42.2	1¼ 32	0.4 0.2
1½ 40	1.900 48.3	1¼ 32	0.5 0.2
2 50	2.375 60.3	1 25	0.5 0.2
2½ 65	2.875 73.0	1 25	0.7 0.3
3 80	3.500 88.9	1 25	1.1 0.5
4 100	4.500 114.3	1½ 29	2.8 1.3
5 125	5.563 141.3	1½ 29	4.0 1.8
6 150	6.625 168.3	1¾ 33	6.0 2.7
8 200	8.625 219.1	1½ 38	12.5 5.7
10 250	10.750 273.1	1½ 38	21.9 9.9
12 300	12.750 323.9	1½ 38	33.8 15.3

Additional sizes available, see Gruvlok Catalog or contact an AnvilStar Representative.

MATERIAL SPECIFICATIONS

CAST FITTINGS:

Cast Iron conforming to ASTM A-536
Ductile Iron conforming to ASTM A-536
Malleable Iron conforming to ASTM A-47

COATINGS:

Rust inhibiting paint Color: ORANGE (standard) or
Hot Dipped Zinc Galvanized conforming to ASTM A-153 (optional)
Other available options: Example: RAL3000 or RAL9000 Series

PROJECT INFORMATION

APPROVAL STAMP

Project:	<input type="checkbox"/> Approved
Address:	<input type="checkbox"/> Approved as noted
Contractor:	<input type="checkbox"/> Not approved
Engineer:	Remarks:
Submittal Date:	
Notes 1:	
Notes 2:	