



**QUICK RESPONSE**  
**AUTOMATIC SPRINKLERS**  
**GL SERIES**  
**UPRIGHT • PENDENT**  
**VERTICAL SIDEWALL**  
**HORIZONTAL SIDEWALL**  
**CONVENTIONAL (OLD STYLE)**

**DESCRIPTION AND OPERATION**

The Globe Quick Response GL Series Sprinklers are a low profile yet durable design which utilizes a 3mm frangible glass ampule as the thermosensitive element. This provides sprinkler operation approximately six times faster than ordinary sprinklers. While the Quick Response Sprinkler provides an aesthetically pleasing appearance, it can be installed wherever standard spray sprinklers are specified when allowed by the applicable standards. It offers the additional feature of greatly increased safety to life and is available in various styles, orifices, temperature ratings and finishes to meet many varying design requirements. Quick Response Sprinklers should be used advisedly and under the direction of approving authorities having jurisdiction.

The heart of Globe's GL Series sprinkler proven actuating assembly is a hermetically sealed frangible glass ampule that contains a precisely measured amount of fluid. When heat is absorbed, the liquid within the bulb expands increasing the internal pressure. At the prescribed temperature the internal pressure within the ampule exceeds the strength of the glass causing the glass to shatter. This results in water discharge which is distributed in an approved pattern depending upon the deflector style used.


The sprinkler and escutcheon are not factory assembled. Assembly is done in the field.



**QUICK RESPONSE**  
**UPRIGHT                      CONVENTIONAL**



**QUICK RESPONSE**  
**PENDENT                      VERTICAL SIDEWALL**



**QUICK RESPONSE**  
**HORIZONTAL SIDEWALL**

**TECHNICAL DATA**

- See reverse side for Approvals and Specifications.
- Temperature Ratings - 135°F (57°C), 155°F (68°C), 175°F (79°C), 200°F (93°C), 286°F (141°C)
- Water Working Pressure Rating - 175 psi (12 Bars)
- Factory tested hydrostatically to 500 psi (34 Bars)
- Maximum low temperature glass bulb rating is -67°F (-55°C)
- Frame - bronze • Deflector - brass • Screw - brass
- Bulb seat - copper • Spring - nickel alloy • Seal - teflon
- Bulb - glass with alcohol based solution, 3mm size

**• SPRINKLER TEMPERATURE RATING/CLASSIFICATION and COLOR CODING**

CLASSIFICATION	AVAILABLE SPRINKLER TEMPERATURES		BULB COLOR	N.F.P.A. MAXIMUM CEILING TEMPERATURE			
	135°F/155°F	57°C/68°C		175°F/200°F	79°C/93°C	286°F	141°C
ORDINARY	100°F	38°C	ORANGE/RED	150°F	66°C	225°F	107°C
INTERMEDIATE			YELLOW/GREEN				
HIGH			BLUE				

# QUICK RESPONSE

## AUTOMATIC SPRINKLERS

### GL SERIES

#### UPRIGHT • PENDENT • VERTICAL SIDEWALL

#### HORIZONTAL SIDEWALL • CONVENTIONAL (OLD STYLE)

### SPECIFICATIONS

NOMINAL "K" FACTOR		THREAD SIZE	LENGTH <sup>1</sup>	FINISHES
2.8	(39 metric)	1/2" NPT	2 1/4" (5.7 cm)	Factory Bronze
4.2	(59 metric)	1/2" NPT	2 1/4" (5.7 cm)	Satin Chrome <sup>2</sup>
5.6	(80 metric)	1/2" NPT	2 1/4" (5.7 cm)	Bright Chrome
7.8	(111 metric)	1/2" NPT	2 1/4" (5.7 cm)	White Polyester <sup>3</sup>
8.1	(116 metric)	3/4" NPT	2 7/16" (6.2 cm)	Black Polyester <sup>3</sup>
				Lead Coated <sup>2</sup>

NOTE: METRIC CONVERSIONS ARE APPROXIMATE.

<sup>1</sup> HORIZONTAL SIDEWALL IS 2 9/16".

<sup>2</sup> FINISHES AVAILABLE ON SPECIAL ORDER.

<sup>3</sup> AVAILABLE AS cULus LISTED CORROSION RESISTANT WHEN SPECIFIED ON ORDER.

### APPROVALS

STYLE	SIN MODEL	K FACTOR	135°F 57°C	155°F 68°C	175°F 79°C	200°F 93°C	286°F 141°C	cULus	F.M.	LPC	CE	NYC - DOB MEA 101-92-E
UPRIGHT	GL2815	2.8	X	X	X	X	X	X	---	---	---	X
	GL4215	4.2	X	X	X	X	X	X	---	---	---	X
	GL5615	5.6	X	X	X	X	X	X	X	X	X	X
	GL8115	7.8*	X	X	X	X	X	X	X	---	---	X
	GL8118	8.1	X	X	X	X	X	X	X	X	X	X
PENDENT	GL2801	2.8	X	X	X	X	X	X	---	---	---	X
	GL4201	4.2	X	X	X	X	X	X	---	---	---	X
	GL5601	5.6	X	X	X	X	X	X	X	X	X	X
	GL8101	7.8*	X	X	X	X	X	X	X	---	---	X
	GL8106	8.1	X	X	X	X	X	X	X	X	X	X
VERTICAL SIDEWALL†	GL5632	5.6	X	X	X	X	X	X	X	---	---	---
	GL8133	8.1	X	X	X	X	X	X	---	---	---	---
HORIZONTAL SIDEWALL §	GL2826	2.8	X	X	X	X	X	X	---	---	---	X
	GL4226	4.2	X	X	X	X	X	X	---	---	---	X
	GL5626	5.6	X	X	X	X	X	X	X	---	---	X
CONVENTIONAL (OLD STYLE)	GL8127	8.1	X	X	X	X	X	X	---	---	---	---
	GL5624	5.6	X	X	X	X	X	---	---	X	X	---
	GL8125	8.1	X	X	X	X	X	---	---	X	X	---

§ HORIZONTAL SIDEWALL cULus LISTED FOR DEFLECTOR 4" TO 12" BELOW THE CEILING, FM APPROVED 4" TO 6".

† VERTICAL SIDEWALL SPRINKLER cULus LISTED FOR LIGHT HAZARD ONLY.

PENDENT VERTICAL SIDEWALL cULus LISTED FOR 6' MIN. SPACING.

UPRIGHT VERTICAL SIDEWALL cULus LISTED FOR 9' MIN. SPACING.

\*1/2" NPT.

### ORDERING INFORMATION

SPECIFY

- Quantity • Model Number • Style
- Orifice • Thread Sizes • Temperature
- Finishes desired
- Quantity - Wrenches - P/N 325390 (1/2"); P/N 312366 (L.O.)

### GLOBE® PRODUCT WARRANTY

Globe agrees to repair or replace any of its own manufactured products found to be defective in material or workmanship for a period of one year from date of shipment.

For specific details of our warranty please refer to Price List Terms and Conditions of Sale (Our Price List).



4077 AIRPARK DRIVE, STANDISH, MICHIGAN 48658

989-846-4583

FAX 989-846-9231

1-800-248-0278

www.globesprinkler.com